



# HEBEI RUITONG WIRE MESH CO., LTD

## Specifications List of Steel gratings

No.	Item	Description
1	Bearing bar	25×3, 25×4, 25×4.5, 25×5, 30×3, 30×4, 30×4.5, 30×5, 32×5, 40×5, 50×5, 65×5, 75×6, 75×10—100×10mm etc; I bar: 25×5×3, 30×5×3, 32×5×3, 40×5×3 etc US standard: 1"x3/16", 1 1/4"x3/16", 1 1/2"x3/16", 1"x1/4", 1 1/4"x1/4", 1 1/2"x1/4", 1"x1/8", 1 1/4"x1/8", 1 1/2"x1/8" etc.
2	Bearing bar pitch	12.5, 15, 20, 23.85, 25, 30, 30.16, 30.3, 32.5, 34.3, 35, 38.1, 40, 41.25, 60, 80mm etc. US standard: 19-w-4, 15-w-4, 11-w-4, 19-w-2, 15-w-2 etc.
3	Cross bar	5×5, 6×6, 8×8mm (twisted bar or round bar)
4	Cross bar pitch	40, 50, 60, 65, 76, 100, 101.6, 120, 130mm or as customers' requirement.
5	Surface treatment	Black, Hot dip galvanized, Cold dip galvanized, Painted, Powder coated, or as customers' requirement.
6	Flat bar type	Plain, Serrated (tooth-like), I bar (I section)
7	Material standard	ASTM A36, A1011, A569, Q235, S275JR, SS304, Mild steel & Low carbon steel, etc
8	Galvanizing standard	CN: GB/T13912, US: ASTM (A123), UK: BS729
9	Steel grating standards	A. China: YB/T4001-1998
		B. USA: ANSI/NAAMM (MBG 531-88)
		C. UK: BS4592-1987
		D. Australia: AS1657-1988
		E. Japan: JJS

Tel: +86-311-85853589 15533962802

Email: info@kg-wiremesh.com

Address: 1-2-3508 kongzhong huayuan, yuhua area, SJZ, China