



HEBEI RUITONG WIRE MESH CO., LTD

Specification of Perforated Meta

material	thickness (mm)	Aperture (mm)	hole spacing (mm)	wide (m)	length (m)	punching rate (%)	weight (kg/m ²)
Coil sheet	0.2	6	2	1	20	44	0.88
	0.35	5	4	1	20	24	2
	0.45	6	3	1	20	35	2.5
	0.8	3	3	1	20	19.6	3
Flat sheet	0.5	1	1	1	2	19.6	3.14
	0.8	1.5	1.5	1	2	19.6	5
	1.5	2	2	1	2	19.6	9.4
	3	5	16	1	2	19.6	18.8
Flat sheet	0.5	1	1	1	2	19.6	3.14
	0.8	1.5	1.5	1	2	19.6	5
	1.5	2	2	1	2	19.6	9.4
	3	5	16	1	2	19.6	18.8
stainless metal plate	0.5	1	1	1	2	19.6	3.14
	0.8	1.5	1.5	1	2	19.6	5
	1	2	2	1	2	19.6	6.28
	2	5	16	1	2	19.6	6.28
aluminium plate	0.5	1	1	1	2	19.6	1.08
	0.8	3	3	1	2	19.6	1.72
	1.5	2	2	1	2	19.6	3.24
	2	4	16	1	2	19.6	4.23

Tel: +86-311-85853589 15533962802

Email: info@kg-wiremesh.com

Address: 1-2-3508 kongzhong huayuan, yuhua area, SJZ, China