



HEBEI RUITONG WIRE MESH CO., LTD

Titanium Wire Mesh Technique Information

Mesh (Wires/ in.)	Wire diameter (in.)	Width of opening (in.)	Open area (%)
4 × 4	0.0320	0.2180	76.00
4 × 4	0.0350	0.2150	74.00
6 × 6	0.0320	0.1350	65.60
7 × 7	0.0250	0.1180	68.20
8 × 8	0.0320	0.0930	55.40
9 × 9	0.0320	0.0790	50.60
10 × 10	0.0350	0.0650	42.30
10 × 10	0.0300	0.0700	49.00
10 × 10	0.0250	0.0750	56.30
12 × 12	0.0110	0.0723	75.30
14 × 14	0.0160	0.0550	60.20
16 × 16	0.0060	0.0565	81.70
18 × 18	0.0100	0.0460	67.40
18 × 18	0.0110	0.0445	64.40
18 × 18	0.0160	0.0400	50.8
20 × 20	0.0030	0.0470	88.40
20 × 20	0.0200	0.0300	36.00
20 × 20 TW	0.0160	0.0340	46.20
24 × 24	0.0100	0.0320	57.90
24 × 24	0.0118	0.0299	51.40
26 × 26	0.0100	0.0290	54.90
30 × 30	0.0100	0.0233	49.00
32 × 32	0.0100	0.0210	46.50
35 × 35	0.0080	0.0206	51.80
40 × 40	0.0050	0.0200	64.00
40 × 40	0.0100	0.0150	36.00

Tel: +86-311-85853589 15533962802

Email: info@kg-wiremesh.com

Address: 1-2-3508 kongzhong huayuan, yuhua area, SJZ, China



HEBEI RUITONG WIRE MESH CO., LTD

Titanium Wire Mesh Technique Information

Mesh (Wires/ in.)	Wire diameter (in.)	Width of opening (in.)	Open area (%)
50 × 50	0.0090	0.0110	30.30
50 × 50 TW	0.0040	0.0160	64.00
60 × 60 TW	0.0090	0.0077	21.30
90 × 90	0.0040	0.0071	41.00
100 × 100	0.0020	0.0080	64.00
120 × 120 TW	0.0040	0.0043	27.00
150 × 150 TW	0.0027	0.0040	35.50

Tel: +86-311-85853589 15533962802

Email: info@kg-wiremesh.com

Address: 1-2-3508 kongzhong huayuan, yuhua area, SJZ, China